



15. IGNITION SYSTEM



IGNITION CIRCUIT



15. IGNITION SYSTEM

SERVICE INFORMATION.....	15-1	IGNITION COIL	15-4
TROUBLESHOOTING	15-2	PULSER COIL	15-6
CDI UNIT INSPECTION	15-3		

SERVICE INFORMATION

GENERAL INSTRUCTIONS

- Check the ignition system according to the sequence specified in the Troubleshooting. (⇒ 1-28)
- The ignition system adopts CDI unit and the ignition timing cannot be adjusted.
- If the timing is incorrect, inspect the CDI unit and A.C. generator and replace any faulty parts. Inspect the CDI unit with a CDI tester
- Loose connector and poor wire connection are the main causes of faulty ignition system. Check each connector before operation.
- Use of spark plug with improper heat range is the main cause of poor engine performance.
- The inspections in this section are focused on maximum voltage. The inspection of ignition coil resistance is also described in this section.
- Inspect the ignition switch according to the continuity table specified in page 20-3.
- Inspect the spark plug referring to Section 3.
- Remove the A.C. generator and pulser coil referring to Section 10.

SPECIFICATIONS

Item		Standard	
Spark plug	Standard type	C7HSA(NGK)	
	Hot type	C6HSA(NGK)	
	Cold type	C8HSA(NGK)	
Spark plug gap		0.6_ 0.7mm	
Ignition timing	“F” mark	13° BTDC/1,700±100rpm	
	Full advance	27° BTDC/5,000±100rpm	
Ignition coil resistance	Primary coil		
	Secondary coil	with plug cap	0.1_ 1.0Ω
		without plug cap	7_ 12KΩ
Pulser coil resistance (20°C)		3_ 5KΩ	
Pulser coil resistance (20°C)		40_ 300Ω	
Ignition coil primary side max. voltage		12V min.	
Pulser coil max. voltage		2.1V min.	

TESTING INSTRUMENT

Kowa Electric Tester

or commercially available electric tester with resistance over 10MΩ/CDV

15. IGNITION SYSTEM

TROUBLESHOOTING

High voltage too low

- Weak battery or low engine speed
- Loose ignition system connection
- Faulty CDI unit
- Faulty ignition coil
- Faulty pulser coil

Normal high voltage but no spark at plug

- Faulty spark plug
- Electric leakage in ignition secondary circuit
- Faulty ignition coil

Good spark at plug but engine won't start

- Faulty CDI unit or incorrect ignition timing
- Improperly tightened A.C. generator flywheel

No high voltage



- Faulty ignition switch
- Faulty CDI unit
- Poorly connected or broken CDI ground wire
- Dead battery or faulty regulator/rectifier
- Faulty ignition coil connector
- Faulty pulser coil

15. IGNITION SYSTEM

CDI UNIT INSPECTION

Remove the two battery cover screws.
 Disconnect the CDI coupler and remove the CDI unit.
 Measure the resistance between the terminals using the electric tester..

- *
- Due to the semiconductor in circuit, it is necessary to use a specified tester for accurate testing. Use of an improper tester in an improper range may give false readings.
 - Use a Sanwa Electric Tester or Kowa Electric Tester.
 - In this table, “Needle swings then returns” indicates that there is a charging current applied to a condenser. The needle will then remain at “∞” unless the condenser is discharged.



Unit: K \square

Probe \oplus (-)Probe	Black	Black/ Yellow	Blue/ Yellow	Green
Black		∞	1k~	20~60
Black/ Yellow	30~80		150~40 0	5~15
Blue/ Yellow	100~250	∞		40~90
Green	10~30	∞	60~200	

15. IGNITION SYSTEM

IGNITION COIL

REMOVAL

Remove the frame body cover. (⇒2-2)
Remove the spark plug cap.
Disconnect the ignition coil wires and remove the ignition coil bolt and ignition coil.

Ignition Coil



INSPECTION

CONTINUITY TEST

* This test is to inspect the continuity of ignition coil.

Measure the resistance between the ignition coil primary coil terminals.

Resistance: 0.1_ 1.0 \square /20 $^{\circ}$ C

Measure the secondary coil resistances with and without the spark plug cap.

Resistances:

(with plug cap): 7_ 12K \square /20 $^{\circ}$ C

(without plug cap): 3_ 5K \square /20 $^{\circ}$ C

* Correctly operate the tester following the manufacturer's instructions.

1. Turn the CDI tester changeover switch to 12V and connect the ignition coil to the tester.
2. Turn the tester power switch ON and check the spark from the watch window.
_Good : Normal and continuous spark
_Faulty : Weak or intermittent spark

15. IGNITION SYSTEM

PULSER COIL INSPECTION

- * This test is performed with the stator installed in the engine.

Remove the frame body cover. (⇒2-2)
Disconnect the A.C. generator connector.



Measure the pulser coil resistance between the blue/yellow and green wire terminals.

Resistance: 40_ 300 \square /20°C

Refer to page 14-6 for the A.C. generator removal.

IGNITION TIMING INSPECTION

- * The CDI unit is not adjustable. If the ignition timing is incorrect, inspect the CDI unit, pulser coil and A.C. generator and replace any faulty parts.

Remove the timing hole cap.



Timing Hole Cap

Warm up the engine and check the ignition timing with a timing light.
When the engine is running at 1700rpm, the ignition timing is correct if the "F" mark aligns with the index mark within $\pm 3^\circ$.

Ignition Timing: 13° BTDC/1700rpm

